

PosterVue Data Sheet

Product Code: CFNAPV

As at 8 September 2016

Applications	Non-adhesive interior mount to small format building windows graphics and glass doors including refrigerated, for POP and retail poster applications. Ideal for re-locate and/or re-use type requirements. Refer to the Recommended Applications Fact Sheet.
Makeup	Calendered monomeric flexible perforated black (no adhesive) / white (printable side) gloss PVC (no adhesive layer) and single layer non-perforated white PE liner.
Vinyl Thickness	304 microns, approx.
Release Liner	177 microns, approx.
Adhesive	No adhesive layer
Perforation Size and Pattern	1.5mm, 35% / 65% open/closed areas
Standard Widths/Lengths	1370mm x 30.48m on 76mm core
Dimensional Stability	Fair. Not suitable on full sun windows.
Application Temperatures	Depends on mounting materials and method used, refer to adhesive specifications.
Service Temperatures	-17°C to +60°C
Expected Lifetime Interior	12 months. Depends on mounting materials and method used.
Water & Humidity Resistance	Good water resistance, fair humidity resistance
Solvent Resistance	Good
Storage Stability	9 months shelf life when stored at 21°C & 50% relative humidity
Printing	Refer to the Ink Compatibility Fact Sheet. Compatible with screen, solvent, latex (may not detect media position, use lowest heat settings), thermal transfer, electrostatic transfer and airbrushing. Print image on white side. Testing recommended before production to determine appropriate profile settings.
Out Gassing	3 to 5 days when suspended vertically in ventilated area. Trim after out gas period.
Matching Overlaminates	Not applicable.
Installation	Refer to the Surface Preparation and Installation Instruction Fact Sheets. Attach to interior surface of clean, dry glass door or window using a clear adhesive tape. Use single or double sided optically clear laminate film slitted to minimum 15mm width is recommended for mounting. Apply to all edges. Maximum recommended sheet size for mounting is one square metre.
Removal	Remove by peeling from surface. Remove and discard tape. Re-apply graphic at a later time or onto another window with fresh new tape.
Warranty and Disclaimer	12 months from date of sale to distributor. Refer to the Warranty Statement.

The information in this data sheet is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. **In all cases, purchasers should independently determine, prior to use, the suitability of this product for their specific application.**