

Applications	Non-adhesive interior mounted graphics to flat building windows and glass doors for retail and commercial applications, so that it cannot be vandalised from the outside. Suited for poster size graphics (<1 sqm). Can also be used as an outdoor or pull-up banner film. To adhere to transparent surfaces, use a double sided adhesive 25mm tape on all four edges. Do not die cut to artwork or letter shapes. Sheet form only.
Makeup	Flexible perforated white (no adhesive) / white (printable side) matt PET film and single layer non-perforated white PET liner.
Vinyl Thickness	180 microns, approx.
Release Liner	50 microns, approx.
Adhesive	No adhesive layer. Use a double sided adhesive 25mm tape around all four edges.
Perforation Size and Pattern	1.5mm, 40% / 60% open/closed areas.
Standard Widths/Lengths	1370mm x 30m on 76mm core.
Dimensional Stability	Excellent. No shrinkage in X and Y axes. Test method FINAT TM14.
Application Temperatures	Refer to OptiTape technical data sheet.
Service Temperatures	-20°C to +100°C without tape. Refer to OptiTape technical data sheet.
Expected Lifetime Interior	3 years.
Water & Humidity Resistance	Good – when interior mounted.
Storage Stability	1 year shelf life when stored out of direct sunlight at 23°C & 50% relative humidity.
Printing	Refer to the Ink Compatibility Fact Sheet. Compatible with solvent (including mid and eco), latex. Print image on white side that does not have a backing liner. <b>Testing recommended before production to determine appropriate profile settings.</b>
Out Gassing	1 to 3 days when suspended vertically in ventilated area. Trim after out gas period.
Installation	<p><b>For transparent surfaces:</b> Refer to the Surface Preparation Instructions. Install in sheet form only, do not die cut to shapes or letters. Dry apply permanent adhesive side of double-sided tape (not supplied with RetailVue) to every edge on the printed side. In your workshop, remove RetailVue liner. At the job site, clean glass with mild soapy water. Remove other side of adhesive tape liner. Dry apply to interior surface of clean glass surface.</p> <p><b>For retractable stands:</b> Trim to dimensions appropriate for the stand. Mount bottom and top edges of trimmed film in accordance to manufacturer's instructions.</p> <p><b>For outdoor banner use:</b> Trim to dimensions appropriate for the banner. Eyelet 1cm from edge in all corners. Add extra eyelets 1cm from edges as required.</p>
Removal	Remove by peeling from surface.
Warranty and Disclaimer	<p>12 months from date of purchase. Refer to the Warranty Statement.</p> <p>The information in this data sheet is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. <b>In all cases, purchasers should independently determine, prior to use, the suitability of this product for their specific application.</b></p>