

BannerVue Data Sheet

Product Code: BVPL30SL

As at 1 June 2021

Applications	Non-adhesive interior mounted graphics to flat building windows and glass doors including refrigerated, for POP/POS, retail applications and shop/business signage. Also suitable for re-locate and/or re-use type requirements for poster size graphics up to 1 sqm. To adhere to transparent surfaces, use a clear double-sided adhesive tape. Can also be used as a pull up/retractable banner film or a banner when eyeletted.
Makeup	Flexible perforated black (no adhesive) / white (printable side) matt PET film and single layer non-perforated white PET liner.
Thickness	Face film 200 microns, approx. Release liner 50 microns, approx.
Adhesive	No adhesive layer. Use 3M 9088-200 clear double sided adhesive 24mm wide tape around all edges to interior mount film to window or door.
Perforation Size and Pattern	1.5mm, 30% / 70% open/closed areas.
Standard Widths/Lengths	1370mm x 30m on 76mm core.
Dimensional Stability	Excellent. No shrinkage in X and Y axes. Test method FINAT TM14.
Application Temperatures	Refer to 3M 9088-200 technical data sheet.
Service Temperatures	-20°C to +100°C without tape, refer to 3M 9088-200 technical data sheet.
Expected Lifetime Interior	3 years.
Water & Humidity Resistance	Good – when interior mounted.
Storage Stability	1 year shelf life when stored out of direct sunlight at 23°C & 50% relative humidity.
Printing	Refer to the Ink Compatibility Fact Sheet. Compatible with solvent and latex ink printers. Print image on white side. Recommend printing 25mm black border around all sides. Testing recommended before production to determine appropriate profile settings.
Out Gassing	1 to 3 days when suspended vertically in ventilated area. Trim after out gas period.
Cutting and Finishing	Do not contour cut or laminate. Can be eyeletted, use 2 or 3 layers of BannerVue per eyelet.
Installation	<p>For transparent surfaces: Refer to our Surface Preparation Instructions and the 3M 9088-200 data sheet. Apply 24mm 3M 9088-200 around all edges to printed image side within the printed black border region, do not overlap in the corners. In the workshop, remove BannerVue liner. At the job site, remove liner of 3M 9088-200 tape. Dry apply to clean glass surface.</p> <p>For retractable stands: Trim to dimensions appropriate for the stand. Mount bottom and top edges of trimmed film in accordance with manufacturer's instructions.</p>
Removal	Remove by peeling from surface. For poster size graphics up to 1 sqm, remove and discard tape. Re-apply graphic later with new 24mm 3M 9088-200.
Warranty and Disclaimer	12 months from date of purchase. Refer to the Warranty Statement.

The information in this data sheet is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. **In all cases, purchasers should independently determine, prior to use, the suitability of this product for their specific application.**