

JetVue Data Sheet

Product Code: CFJVWL

As at 8 February 2018

Applications	Exterior mount to windows and glass doors for POP posters, retail and commercial window signage. Has an inkjet receptive top coating.		
Makeup	Calendered polymeric flexible perforated black (adhesive side) / white (printable side) PVC with clear pressure-sensitive adhesive and a patented release liner consisting of white PET film laminated to perforated paper. Features an ultra-thin aqueous inkjet-receptive top coat.		
Vinyl Thickness	203 microns, approx.		
Release Liner	178 microns, approx.		
Adhesive	25 microns, approx. Removable acrylic adhesive		
Perforation Size and Pattern	2.0mm, 50% / 50% open/closed areas		
Transmittance	VLT 36.8%		
Standard Widths/Lengths	914mm x 15.24m on 76mm core		
Dimensional Stability	Good		
Application Temperatures	Recommended:	15°C to 25°C,	Min: 4°C Max: 30°C (in shade)
Service Temperatures	-17°C to +60°C		
Expected Lifetime Exterior	12 - 18 months. 6 months for clean removal. Adhesion may increase with time. Use of clear coat or overlamine is recommended to preserve printed image.		
Water & Humidity Resistance	Fair, recommend to overlamine with a compatible optically clear film.		
Solvent Resistance	Good		
Storage Stability	12 months shelf life when stored at 21°C & 50% relative humidity		
Printing	Designed for pigmented or dye based aqueous inkjet inks. Testing recommended before production to determine appropriate profile settings.		
Installation	Refer to the Surface Preparation and Installation Instruction Fact Sheets. Apply to clean, dry, tepid temperature glass surface. Use mild liquid soap (wax free) and water, dry glass well with clean lint free cloth and 100% IPA. Do NOT use ammonia, Windex®, vinegar, methylated spirits, Prep-Wash, Prep-Sol, citrus cleaners or other solvent-based glass cleaner prior to application. Do not use heat.		
Care and Removal	Refer to the Care and Removal Fact Sheet. Remove by peeling from surface.		
Warranty and Disclaimer	<p>12 months from date of sale to distributor. Refer to the Warranty Statement.</p> <p>The information in this data sheet is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for application or otherwise create guarantees of product performance. In all cases, purchasers should independently determine, prior to use, the suitability of this product for their specific application.</p>		