

SuperVue™ Data Sheet

Product Code: CFEABWSV

As at 5 April 2016

Applications	Exterior mount to vehicles windows, building wraps and other large format window graphic requiring top of the range in quality, no risk, type of film. High tolerance in challenging installation conditions. Conformable to curved glass surfaces. Refer to the Recommended Applications and Visible Light Transmission Compliance Fact Sheets.		
Makeup	Calendered polymeric flexible perforated black (adhesive side) / white (printable side) gloss PVC with clear pressure-sensitive adhesive and dual layer liner comprising clear plastic PET liner laminated to perforated paper layer.		
Vinyl Thickness	203 microns, approx.		
Release Liner	178 microns, approx.		
Adhesive	25 microns, approx. Removable acrylic adhesive		
Perforation Size and Pattern	2.0mm, 50% / 50% open/closed areas		
Transmittance	VLT 36.8% on 3.5mm factory tinted automotive glass		
Standard Widths/Lengths	1370mm x 30.48m on 76mm core		
Dimensional Stability	Good		
Application Temperatures	Recommended: 15°C to 25°C, Min: 4°C Max: 30°C (in shade)		
Service Temperatures	-17°C to +60°C		
Expected Lifetime Exterior	2 - 3 years. 6 months for clean removal. Adhesion may increase with time.		
Water & Humidity Resistance	Fair, recommend to laminate with optically clear film		
Solvent Resistance	Good		
Storage Stability	9 months shelf life when stored at 21°C & 50% relative humidity		
Printing	Refer to the Ink Compatibility Fact Sheet. Compatible with screen, solvent, UV cure, thermal transfer, electrostatic transfer and airbrushing. Print image on white side. Testing recommended before production to determine appropriate profile settings.		
Out Gassing	3 - 5 days when suspended vertically in ventilated area. Trim after out gas period.		
Matching Overlamine	Clear Focus CurvaLam		
Installation	Refer to the Surface Preparation and Installation Instruction Fact Sheets. Apply to clean, dry, tepid temperature glass surface. Use mild liquid soap (wax free) and water, dry glass well with clean lint free cloth and 100% IPA. Do NOT use ammonia, Windex®, vinegar, methylated spirits, Prep-Wash, Prep-Sol, citrus cleaners or other solvent-based glass cleaner prior to application. Do not use heat.		
Care and Removal	Refer to the Care and Removal Fact Sheet. Remove by peeling from surface.		
Warranty and Disclaimer	12 months from date of sale to distributor. Refer to the Warranty Statement.		

The information in this data sheet is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for application or otherwise create guarantees of product performance. **In all cases, purchasers should independently determine, prior to use, the suitability of this product for their specific application.**